



The Leader in Retrofitting Pressbrakes and Shears

Easygag Price List

Easygag

The Chain Drive Easygag rail is a workhorse which features a 4.5" high smooth fence and a flip mechanism to move the stop out of the way when workpieces exceed the travel length of your system. The 2" x 4.5" heavy duty extrusion is sturdy, durable and its open design makes it easy to service.

CD is driven by a 10:1 gear reduced D.C. servo motor. A 100 watt DC servo holds the stop once the motor arrives in position. The stop is traversed using a standard #31 roller chain which is virtually indestructible and readily available off-the-shelf. A T-slot and mounting bolts are provided along the bottom for mounting. The DC servo generates enough torque to move a 100 lb. load over a roller table.

Length	Model	The Multi-Job Control
3'	EG-36CD	\$5,755.00
6'	EG-72CD	\$5,990.00
10'	EG-120CD	\$6,420.00
12'	EG-144CD	\$6,985.00
14'	EG-168CD	\$8,505.00

NOTE: The length specified is total travel. The physical size is approximately 2 feet longer than the travel length.

Easygag Options:

DP-4 Display Pendant Mount Assembly \$ 420.00

10' Roller Table: 10" wide, 12 gauge powder coated frame 1.9" rollers on 1.5" centers. The Easygag drive is mounted to the table when ordered. Tables can be linked to each other and mounted on the opposite side of the sawing device for feeding or off-loading. Capacity is 350 lbs. per section. **\$1,095.00**

Support legs for roller table: Consists of an H-style leg to support one end of the table. Height adjustment is 31" to 43". Powder coated finish. 2 legs required for free standing table. **\$ 180.00**

8' Solid Table: 15" wide table can be used to mount the Easygag on either side. Can also be used as an in-feed or out-feed table. Order legs separately. **\$1,070.00**

Support Legs for Solid Table: One leg required for each end of free standing table. Adjustable height from 31" to 43". **\$ 180.00**

Scanner Package: Includes barcode scanner and barcode scanner interface. Allows cut lists to be scanned directly into the Easygag control. **\$1,310.00**

Auto Advance Switch and Cable: Used for sequential positioning. Mount this on the up-action of the punch or saw to advance the Easygag on each cycle. **\$ 220.00**

Output Relay, Socket and Cable: Use this 24V relay to fire an external device like a saw, punch or ready light. The relay fires when the Easygag reaches position. **\$ 220.00**

NOTE: When BOTH an Auto Advance Switch and Output Relay are ordered, a single cable feeds both devices from the Easygag Control.

Shock Absorber: Adjustable tension shock absorber mounts in place of standard stop to absorb impact from loading workpieces. **\$ 205.00**

Installation Assistance and Training: Includes assistance with layout and installation. End user must provide assistance and be prepared to make brackets, supports, etc. **\$2,950.00**

NOTES

AC Power Requirements: Automec gauging systems require 105 to 125VAC, 60HZ at 7 AMPS on an isolated line. If this power is not available a 2.0 KVA step down transformer should be used. Do **NOT** use press brake control transformer. Supplying this power to the system is the end user responsibility.

Floor Anchoring: Some Automec systems require anchoring to the floor. This function is not performed by the Automec installer and is the responsibility of the end user.